

Use and Care of your Magnetic Sign

Vehicle Preparation

Both the vehicle surface and the magnetic side of the sign should be clean, dry and waxed prior to applying.

How to Apply your Magnetic Sign

Let one edge of the sign contact the vehicle in the desired position. Then, let the magnetic power do the work as it puts the sign into place from the edge where you started to the edge opposite. If the sign is not exactly where you want it, peel it off, reposition the starting edge and repeat. Make sure that the entire surface of the sign is smoothly against the vehicle with no air pockets underneath. In winter the temperature of the sign should be about 50°F during installation, but the temperature of the vehicle surface does not matter.

Do any surfaces present problems?

Care should be taken with wood grain paneling and metallic finishes. Such surfaces should be checked weekly. A generous waxing of both the surface where the sign will be placed and the back of the sign itself will help prevent damage. Magnetic signs are **not** recommended for repainted surfaces.

Sign Maintenance

Remove the sign weekly and wipe dry both the magnetic side and the surface of the vehicle. This keeps moisture from collecting, which can potentially damage a vehicle's surface. Cleaning the display side of magnetic sign is just as easy. Simply wash it with warm water and a mild detergent.

Magnetic Sign Storage

Avoid wrinkling by storing around a 3 inch diameter tube with the printed side of the sign **facing out**, or store the signs flat. Since the sign is permanently magnetic, you need not protect against magnetic destruction. Anything else is just common sense; for example, don't put heavy things on or against signs in storage.

Enjoy your quality sign!

©2003, SignCrafters, Inc. All rights reserved.